

Model #7000-EXT
Extender Kit for #7000 A-Frame Ladder

Parts List

4 – Short Extension Boot

4 – 1/4-20 x 2” Bolt

4 – 1/4” Nylon Acorn Nut

Note: For missing or replacement parts, please visit our website at www.conferladders.com.

The Extension Boots are installed onto the bottom ends of the stringers. They will raise the ladder to a height of 56”. Depending on the ground level on the outside of the pool it may not be necessary to use them on the outside legs of the ladder.

- 1. Remove the bottom treads if they have been installed.**
- 2. Using a hacksaw cut the off the small nubs on the sides of the stringers that were holding the bottom treads in place, this will make it easier to slip the extension boots onto the ends of the ladder legs.**
- 3. Slide the four extension boots onto the ends of the ladder legs so that the top angles of the extension legs match the underside angle of the tread. Push the extension boots on until they are fully engaged.**
- 4. Drill a 5/16” hole all the way through each extension boot and fasten with the 1/4-20 x 2” bolt and acorn nut.**
- 5. Reattach the bottom treads to the ends of the extension boots.**



Made in the USA by
CONFER PLASTICS, INC.
97 WITMER ROAD
NORTH TONAWANDA, N.Y. 14120-2421
www.conferladders.com

PRINTED IN USA